

# Optimize Surgical Outcomes with FlowXL<sup>®</sup> Measurements

## FlowXL<sup>®</sup> Flowmeter

An objective measurement of intraoperative flow is essential to assuring vessel patency.

Excel at intraoperative flow measurements with Transonic's next generation FlowXL<sup>®</sup> Flowmeter.

The FlowXL is a standalone, touchscreen flowmeter used during surgery with Transonic's Flowprobes to measure, display, and document absolute volume flow in vessels and other derived parameters. The meter is highly configurable, but easy to use.

## Features

- **Simple Plug & Play Operation:** Turn on the power, plug in a Flowprobe, and measure flow.
- **User-friendly interface:** touchscreen display with simple, intuitive navigation
- **Scalable Hardware:** Standalone meter with multiple mounting options and optional mobile cart/trolley, secondary surgeon display, printer shelf & printer
- **Configurable Software:** QuickFlow or Advanced Flow (coming soon) options allow the user to choose the software functionality that fits their workflows
- **Guaranteed Probe Durability & Reliability:** 12 months or 75 uses



Available in EU and Japan Only

**transonic**  
THE MEASURE OF BETTER RESULTS.

[www.transonic.com](http://www.transonic.com)

# FlowXL<sup>®</sup> Flowmeter



## Configurable Software

### QuickFlow

Quick Flow software has limited functionality for simpler plug & play operation and no internal memory to save data.

1. Measure flow and display flow data and derived parameters
2. Capture and annotate snapshots
3. Print snapshots or export to USB drive

### AdvancedFlow - Coming Soon

AdvancedFlow Software allows the user to measure flows and also save flow data in dedicated patient records.

1. Patient Name and ID# Entry
2. Surgery Type and Vessel Name Entry
3. Multiple Surgeon Name Entry
4. Capture Snapshots or Recordings
5. Create Annotated Reports with Multiple Snapshots
6. Print Snapshots/Reports or Export to USB
7. Set up Admin and Operator Passwords and Permissions
8. Export Patient Records.

## Specifications

### METER DIMENSIONS

**SIZE:** 12.5" W x 9.25" H x 3.5" D  
(31.75cm W x 23.5cm H x 8.9cm D)

**WEIGHT:** 6.5 lbs. (2.9 Kg)

### POWER SUPPLY

**INPUT:** 50-60 Hz; 100-240 VAC +10%  
(automatic voltage adjustment), Output:  
15VDC, 4A

### DISPLAY

12.1" (30.7cm) color, active matrix  
capacitive touchscreen display

### PORTS

Flowsensor Connectors(2),  
Mains Power (100-240VAC) input,  
Type A USB (2),  
Type B mini USB (1),  
DVI-D for secondary display,  
Auxiliary Input (1/4" phono connector)  
for ECG, Ethernet (not active on initial  
release)

### PRINTER

P/N GP0003 - HP Deskjet 3760 for use  
in Europe

### REGULATORY COMPLIANCE

Complies with acceptable standards  
for medical and electrical equipment  
(IEC60601-1). This Transonic<sup>®</sup> products  
is CE marked per 93/42EEC Annex II  
as amended by Directive 2007/47/EEC.  
Transonic<sup>®</sup> is an ISO13485:2016-certified  
facility.